Open Graded Mix

Open Graded Mix is an alternative solution for upgrading deteriorated roads without the need to rebuild from the sub-base.

An environmentally sound solution, providing less pollution and fossil fuel consumption than traditional methods.



FEATURES & BENEFITS

- Self-healing, flexible and long lasting
- Mitigates reflective and thermal cracking
- Improves skid resistance and surface geometrics
- Meets OPSS 309 specifications

FOR MORE INFORMATION AND A FREE ON-SITE CONSULTATION:

1-800-370-9912



AVAILABLE ACROSS ONTARIO

Contact us to find out if this service is available near you.



Open Graded Mix





Open Graded Mix is used to correct pavements with severe cracking or insufficient base.

Open Graded Mix (OGM) is created using an open graded aggregate blend coated with a rich residual asphalt film which fills the voids to prevent bleeding or flushing. OGM provides strength and stability after compaction but remains pliable to avoid long-term issues. Flexible and resistant to cracking, the high voids and rich asphalt emulsion allow the surface to self-heal.

OGM is ideal for areas that have drainage issues or are susceptible to moisture. The open texture of the material improves skid resistance, particularly under wet conditions, minimizing hydroplaning with its draining capabilities.

With minimal maintenance, pavements structured with OGM have been proven to last more than 30 years in Ontario's climate.

AVAILABLE ACROSS ONTARIO

Contact us to find out if this service is available near you.

FOR MORE INFORMATION AND A FREE ON-SITE CONSULTATION:

1-800-370-9912

